

customer access home

searching

patents

documents

TOC

my account

help

view/checkout

log off

My Search Results

- ➔ [Tech Track Results](#)
- ➔ [Retro Search Results](#)
- ➔ [TOC Results](#)
- Patents**
- ➔ [Order Patents](#)
- ➔ [Patent Order History](#)
- Get Started**
- ➔ [Submit a Search](#)
- ➔ [Start a New TOC](#)
- ➔ [Edit My TOCs](#)

Patent Ordering

Enter Patent or NDN Number:

☐ Add patent to cart automatically**42** Patent(s) in Cart**Patent Abstract**

PCT 03-09-00 00012654 WO **REFORMULATED
REDUCED POLLUTION DIESEL FUEL**

INVENTOR(S)- PEDERSEN, Michael, J. 33 Colonial, Irvine, CA
92620 United States of America

APPLICANT(S)- ATLANTIC RICHFIELD COMPANY 2300 West
Plano Parkway, Plano, TX 75075 United States of America

DATE FILED- 1999-08-17

PUBLICATION NUMBER- 00012654 WO

DOCUMENT TYPE- A1

PUBLICATION DATE- 2000-03-09

PATENT PRIORITY INFO- 09/145,189, 1998-09-01, United
States of America

ATTORNEY, AGENT, OR FIRM- CARROLL, Rodney, B., Atlantic
Richfield Company, 2300 West Plano Parkway, Plano, TX 75075,
United States of America

INTERNATIONAL PATENT CLASS- C10L; 1/00; 1/04; 1/08;
1/18; 7/20; F23C; 1/08

PCT APP. NO.- PCT/US99/18622

FILING LANGUAGE- English

LANGUAGE- English NDN- 172-0029-5039-9

A reformulated diesel fuel, a method of making and a method of using the diesel fuel to reduce pollution are disclosed. The diesel fuel meets the requirements of ASTM D975-96a for a low sulfur number 2 diesel fuel and provides reduced emission benefits relative to a certified diesel fuel, certified under Section 2282(g) Title 13, California Code of Regulations and containing less than 15 volume percent aromatics having a natural centane number of at least 55, a sulfur content less than 15 ppmw, a nitrogen content less than 10 ppmw, a polycyclic aromatics content no greater than 1.5 weight percent and an initial boiling point of at least 350 degrees F. The method of making includes hydrotreating stream in a vessel and hydrocracking a stream in a vessel in order to obtain a diesel range fraction which is separated to obtain a diesel fuel and a gasoline fraction.

DESIGNATED COUNTRY(S)- AL; AM; AT; AU; AZ; BA; BB;

BG; BR; BY; CA; CH; CN; CU; CZ; DE; DK; EE; ES; FI; GB; GD;
GE; GH; GM; HR; HU; ID; IL; IN; IS; JP; KE; KG; KP; KR; KZ;
LC; LK; LR; LS; LT; LU; LV; MD; MG; MK; MN; MW; MX; NO;
NZ; PL; PT; RO; RU; SD; SE; SG; SI; SK; SL; TJ; TM; TR; TT;
UA; UG; UZ; VN; YU; ZW; GH; GM; KE; LS; MW; SD; SL; SZ;
UG; ZW; AM; AZ; BY; KG; KZ; MD; RU; TJ; TM; AT; BE; CH;
CY; DE; DK; ES; FI; FR; GB; GR; IE; IT; LU; MC; NL; PT; SE;
BF; BJ; CF; CG; CI; CM; GA; GN; GW; ML; MR; NE; SN; TD; TG

▶ **proceed to checkout**



NERAC, Inc. One Technology Drive . Tolland, CT
Phone (860) 872-7000 . FAX (860) 875-1749 . [Report a Problem](#)
.1995-2001 All Rights Reserved.

[Privacy Statement](#)